




Logmanager logo guidelines


- ✗ LOGmanager
- ✗ LOG manager
- ✗ LOG Manager
- ✗ LOG MANAGER

- ✗ LogManager
- ✗ Log Manager
- ✗ Log manager
- Logmanager ✓

Logmanager 

Basic logomark (or symbol) which can be used separately





For digital use only

RGB 15-15-215
Hex 0F0FD7



For print use only*


CMYK 0 - 0 - 0 - 100

*It is perfectly fine to use only black colour for printing documents such as data sheets, case studies, etc.


Use our blue colour (Pantone 286 C) only when printing materials such as business cards, brochures or flyers in professional printers.

Additional colours

Pantone 072 C
Hex 000695




Hex DDE6F6




Hex F5F8FC



Black
Hex 000000



White
Hex FFFFFFFF



Pantone Warm red C
Hex FF3529



Pantone 802 C
Hex 29CF20



Pantone Yellow C
Hex FFD900





Logmanager 

Logmanager 

Logmanager 

Logmanager 

Logmanager 

Logmanager 

Forbidden colour ways and logo modifications

Logmanager ● 

Logmanager ● 




Logmanager ● 

Logmanager ● 




Logmanager ● 

Logmanager ● 


Logo positioning on different formats



Logomark positioning on different formats



Logo sizing guide in relation to the format





Logmanager logo guidelines