Datasheet

Logmanager is a log management platform enhanced with SIEM capabilities that radically simplifies response to cyberthreats, legal compliance, and troubleshooting.

It is available as either a hardware appliance or a virtual appliance compatible with VMware and HyperV platforms. The hardware requirements for virtual appliances are identical to hardware models specification.

Supported log sources

Logmanager natively supports over 135 sources across all IT domains, including security solutions, networking, virtualization, operating systems, databases, and cloud applications. The extensive list continues to grow with each update. Logmanager also supports standardized structured log formats such as CEF, LEEF, RFP5424, and JSON. For legacy sources, it enables quick and easy creation of customized parsers.

Forwarder

Logmanager Forwarder is a standalone appliance hardware or virtual providing secure and reliable log collection from remote branches and Internet/DMZ.

Logmanager

Logmanager HW Appliances
Recommended Resources for Virtual Appliances

	Logmanager-XXL	Logmanager-XL	Logmanager-L	Logmanager-M	Logmanager-S	Logmanager Forwarder
Performance in EPS[1]	10000	10000	5000	2000	1000	9000
Data Retention in Days	~660-880	~440 – 660	~275 – 550	~230 – 460	~150	N/A; acts as remote buffer
Storage	200 – 240 TB	120 – 160 TB	40 – 80 TB	12 – 24 TB	4TB	250GB
Memory	128GB	128GB	128GB	64GB	64GB	8GB
RAID	RAID 6	RAID 6	RAID 6	RAID 5	RAID 1	N/A
Networking	Two NICs, 2x10Gbps SFP+ redundant, and 4x1Gbps RJ-45	Two NICs, 2x10Gbps SFP+ redundant, and 4x1Gbps RJ-45	Single NIC, 2x10Gbps SFP+, and 4x1Gbps RJ-45	4x 1Gbps RJ-45	4x 1Gbps RJ-45	N/A
Hardware Details	2U server, 2x PSU, Workload Accelerator, 5y NBD RMA, 1-year support renewals or 5-year contract	2U server, 2x PSU, Workload Accelerator, 5y NBD RMA, 1-year support renewals or 5-year contract	2U server, 2x PSU, 5y NBD RMA, 1-year support renewals or 5-year contract	1U server, 2x PSU, 5y NBD RMA, 1-year support renewals or 5-year contract	1U server, 1x PSU, 5y NBD RMA, 1-year support renewals or 5-year contract	MicroPC platform, 5y RMA, 1-year support renewals or 5-year contract

Optional addons and Scaling

Cluster – Allows creation of clusters up to 4 units serving more than 10000 EPS. Cluster DB capacity equals sum of all cluster members capacity divided by two.

[1] **Performance in EPS** – Maximum sustainable load measured in Events Per Second (EPS) for a standalone Logmanager unit, also known as Max Constant EPS. Raw log mix with average size 700 Bytes, tested with full parsing. Peak EPS equals 2x the Max Constant EPS over 10 minutes.

Licensing – All versions include unlimited number of agents, sources and system users.

LOGMANAGER.COM

Logmanager